



Article code: **DY6080**

This lightweight plastic pallet offers an outstanding weight/load ratio. DY6080 features 3 integrated runners, which enables use with conveyor technology as well. The heavy duty, solid body construction accommodates a variety of loading sizes and weights.

TECHNICAL FEATURES	VALUES	LOADING QUANTITIES	VALUES
Dimensions L x W x H (mm) Tol: ± 5 mm	800 x 600 x 135	N° of pallets per stack	52
Weight (kg) Tol: 0/+10%	3,7	Height of stack of pallets (mm)	2230
Pallet entry height (mm)	105	Stacking weight (kg)	192
Height topdeck (mm)	30	N° of pallets per truck load (on 13,6m platform)	1664
Dynamic loading* (kg)	400	N° of pallets per 20' container	160
Static loading* (kg)	800	N° of pallets per 40' HC container	414

*values are referred to test performed with an uniformly distributed load at room temperature (23°C) as established by UNI/ISO 8611-1:2011 standard. Different conditions correspond to different values; it's necessary to test the product before use.

CHARACTERISTICS

Thermal stability: -20°C / +60°C

Stackable: yes

Further option available: external rim

Material: post commercial recycled polypropylene

Standard colours: black, other colours upon request

Marking includes recyclability information, traceability through date of production :



day/month/year

KARTON SpA

Via Europa, 7 – 33077 Sacile (PN) – Italy
Tel. +39 0434 788811 – Fax +39 0434 788822
info@karton.it – www.karton.it

Regulatory Requirements

- Directive 94/62/CE and subsequent amendments.
- Regulation 1907/2006/CE of 18th December 2006 (REACH) and subsequent amendments.
- Other regulatory requirements must be agreed with Karton Sales Department prior to submit commercial order.

Packaging Reference Standards

• EN 13429 Packaging. Reuse.

Pallets are designed as reusable transport packaging. It's a responsibility of the Customer to assess that the product design, as described in this specification, is fit for completing a suitable number of logistic operations and /or rotations in the normally foreseeable using conditions.

• EN 13430 Packaging. Requirements for packaging recoverable by material recycling.

Polypropylene pallets are made of thermoplastic polyolefin 100% recyclable. It's a responsibility of the Customer to assess that the product design ensures effective emptying and packaging sorting system in the normally foreseeable using conditions. The symbol associated to these products is 05 (PP), according to the dispositions of the Association of Plastic Industry.

Environmental label

