

ST 1208 Nestable pallet


RODUCT DATA SHEET ST-GQ-PLT15-GB Rev.1 05/07/23











Article code: ST1208

Sturdy and easy to clean ST1208 nestable pallets are a functional solution to safely transport and store products. Once unloaded, these pallets can be nested for a cost-efficient return trip, saving warehouse storage space. 3 runners available as additional feature, as well as external rim. Standard colour is black, other colours available upon request.

TECHNICAL FEATURES	VALUES	LOADING QUANTITIES	VALUES
Dimensions L x W x H (mm) Tol: ± 5 mm	1200 x 800 x 135 (150 with runners)	N° of pallets per stack	50 / 56
Weight (kg) Tol: 0/+10%	8,9	Height of stack of pallets (mm)	2300 (2500 with runners)
Pallet entry height (mm)	100 (117 with runners)	Stacking weight (kg)	445 (449 with runners)
Height topdeck (mm)	35	N° of pallets per truck load (on 13,6m platform)	1848 (1650 with runners)
Dynamic loading* (kg)	800	N° of pallets per 20' container	576 (without runners)
Static loading* (kg)	2000	N° of pallets per 40′ HC container	1455 (without runners)

^{*}values are referred to test performed with an uniformly distributed load at room temperature (23°C) as estabilished by UNI/ISO 8611-1:2011 standard. Different conditions correspond to different values; it's necessary to test the product before use.

CHARACTERISTICS

Thermal stability: -20°C / +60°C

Nestable: yes (without runners)

Material: recycled polypropylene, may contain mix of polyolefins coming from post consumer waste

Further options available: external rim (included), 3 runners (optional)

Standard colours: black, other colours upon request

Marking includes recyclability information and traceability through date of production:



day/month/year

KARTON SpA

ST 1208 Nestable pallet

PRODUCT DATA SHEET ST-GQ-PLT15-GB Rev.1 05/07/23



Packaging Reference Standards

•EN 13429 Packaging. Reuse.

Pallets are designed as reusable transport packaging. It's a responsibility of the Customer to assess that the product design, as described in this specification, is fit for completing a suitable number of logistic operations and /or rotations in the normally foreseeable using conditions.

•EN 13430 Packaging. Requirements for packaging recoverable by material recycling.

Polypropylene pallets are made of thermoplastic polyolefin 100% recyclable. It's a responsibility of the Customer to assess that the product design ensures effective emptying and packaging sorting system in the normally foreseeable using conditions. The symbol associated to these products is 05 (PP), according to the dispositions of the Association of Plastic Industry.

Environmental label

