

SL 1208 Light Nestable Pallet

PRODUCT DATA SHEET ST-GQ-PLT12-GB Rev.2 06/08/2024



3 runners kit



Article code: SL1208

Sturdy and easy to clean, SL1208 nestable pallets are a functional solution for safe transport and storage of products. Once unloaded, these pallets can be nested for a cost-efficient return trip, saving warehouse storage space. 3 runners available as additional feature, as well as external rim. Standard colour is black, different colours available upon request.

TECHNICAL FEATURES	VALUES	LOADING QUANTITIES	VALUES
Dimensions L x W x H (mm) Tol: ± 5 mm	1200 x 800 x 138 (141 with runners)	N° of pallets per stack	60 (18 with runners)
Weight (kg) Tol: 0/+10%	4,5 (6,2 with runners)	Nestable	Yes (without runners)
Pallet entry height (mm)	107 (110 with runners)	Height of stack of pallets (mm)	2500 (without runners)
Height topdeck (mm)	30	Stacking weight (kg)	310
Loading capacity* (kg)	Dynamic: 500 Static: 1500	N° of pallets per truck load (on 13,6m platform)	1980 (594 with runners)

*values are referred to test performed with an uniformly distributed load at room temperature (23°C) as established by UNI/ISO 8611-1:2021 standard. Different conditions correspond to different values; it's necessary to test the product before use.

CHARACTERISTICS

Thermal stability: -20°C / +60°C

Material: recycled polypropylene, may contain mix of polyolefins coming from post consumer waste that could determine the typical odour

Further options available: external rim, 3 runners kit (optional)

Standard colours: black, other colours upon request

Marking includes recyclability information and traceability through date of production:



day/month/year

KARTON SpA

Via Europa, 7 – 33077 Sacile (PN) – Italy
Tel. +39 0434 788811 – Fax +39 0434 788822
info@karton.it – www.karton.it

Packaging Reference Standards

•EN 13429 Packaging. Reuse.

Pallets are designed as reusable transport packaging. It's a responsibility of the Customer to assess that the product design, as described in this specification, is fit for completing a suitable number of logistic operations and /or rotations in the normally foreseeable using conditions.

•EN 13430 Packaging. Requirements for packaging recoverable by material recycling.

Polypropylene pallets are made of thermoplastic polyolefin 100% recyclable. It's a responsibility of the Customer to assess that the product design ensures effective emptying and packaging sorting system in the normally foreseeable using conditions. The symbol associated to these products is 05 (PP), according to the dispositions of the Association of Plastic Industry.

Environmental label

